

S-Series is optimised to maximise reliability, life-time and efficiency - also in sub-zero temperatures. The fuel cells in the S-series are available in the power ratings 50, 750, 1500 and 3000 W. Fully integrated power units based on cutting-edge technology, innovative solutions and fundamental understanding.

By combining fuel cell units (power) and hydrogen cylinders (energy) economical systems can be configured for a specific application. Integration with methanol reformer is offered on request.

Fuel cells – An alternative if you have low power needs (< 10 kW) and large energy needs (> 10 kWh).



Advantages

- Maintenance free
- No self-discharge
- Known energy capacity
- Cold tolerant
- Heat tolerant
- Load following output
- Longevity
- Low operation cost
- Compact
- Light
- No waste problems or costs
- No emissions

Applications

- Telecom backup power
- Radio communication relay stations
- Emergency transmitters
- Military sensor equipments
- Uninterruptible power supplies (UPS)

Technology

- Control system with optional Internet capabilities and alarm functions via SMS
- Control system is remote upgradeable
- Components optimised for longevity and low power consumption
- Liquid cooling for longevity
- Low pressure air feed for higher efficiency
- Internal humidification for longevity
- CE compliance
- 1 year warranty

Model program

Fuel cell	S-50	S-750	S-1500	S-3000	S-3000 Telecom
Nominal power	50 W	750 W	1500 W	3000 W	3000 W
Current	0-5 A	0-80 A	0-80 A	0-80 A	0-80 A
Voltage output (raw)	12-18 VDC ¹	11-18 VDC ¹	22-36 VDC ¹	43-72 VDC ¹	-57 to -43 VDC ¹
Dimensions (mm)	471x178x413 (19" width, 4 U height)		471x178x513 (19" width, 4 U height)		
Weight (kg)	12	13	14	16	16
Operating time 12-pack ²	100 days	10 days	5 days	60 h	60 h

¹ Raw output voltage span can be specified to a smaller range in software to be compatible with any suitable battery or sensitive equipment

² At nominal power, 12-pack of standard cylinders, pressure 200 bar (e.g. AGA item no. 1541)

Fuel (hydrogen)	4-pack	12-pack	24-pack
Energy	40 kWh	120 kWh	240 kWh
Energy @ 48 VDC	800 Ah	2400 Ah	4800 Ah

Performance

Efficiency (at nominal power)	40 %
Efficiency (at 40 % load)	48 %
FC Start-up time ³ (>0 °C)	5-35 s
FC Start-up time ³ (<0 °C)	1 min – 15 min
Transient behaviour 20%-100% load	< 0,1 s
Power to load at black-out	Seamless with battery

³ Actual start-up time depends on conditions and application. Contact Cellkraft for more information.

Technical data

Fuel	
Quality	Industrial grade hydrogen
Supply pressure	2-8 bar(g)
Connection	6 mm or ¼" Swagelok®
Exhaust	
Composition	Humid air
Temperature	Typical 30-50 °C
Operating conditions	
Ambient temperature in use	-33 till +45 °C
Ambient temperature in storage	-40 till +60 °C
Ambient humidity in use	Non condensing
Ambient humidity in storage	Non condensing
Electrical interface	
Power	Screw terminals (16 mm ²)
RS 232	9 pin female D-sub connector (wiring defined in manual)
Conformance	
General	CE-certification (EMC 89/336/EEC, LVD 93/68/EEC)
Power supply interface*	ETSI EN 300 132-2
Environment*	ETSI EN 300 019-1-3

*S-3000 Telecom

Contacts

Joakim Nordlund
+46 8 673 19 15
joakim.nordlund@cellkraft.se

Anders Ocklind
+46 8 673 19 14
anders.ocklind@cellkraft.se

Cellkraft AB
Björnnäsv. 21
SE-114 19 Stockholm
Sweden

www.cellkraft.se

Cellkraft reserves the right to change data in this document.
Data is binding only after contractual agreement with Cellkraft.

Apr -11 ver: Eng. S.28

Ordering key

S - I II - 0 0

I	Power
	0 50 W
	1 750 W
	2 1500 W
	3 3000 W
4 3000 W telecom	

II	Cold start options
	0 0 °C
	1 -15 °C
	2 -20 °C
3 -30 °C	

An example:

S - 1 1 - 0 0

This is the key for the S-750 with cold start capability from -15 °C.

Pricing example

Power	1 unit	30 units
0	ask	ask
1	220,000	80,000
2	350,000	110,000
3	480,000	150,000
4	480,000	150,000

All prices are in SEK (1 SEK ≈ 0.15 USD ≈ 0.11 EUR). Additional charge for cold capability applies. Ask fore more information.

System integration



Cellkraft fuel cells are modular and can be connected in series or in parallel. The S-Series fuel cells are developed to be easily integrated with AC-DC, DC-DC, DC-AC converters or batteries.

Cellkraft offers complete system solutions for your demand.